DTS 402

LISSMAC
CONSTRUCTION TECHNOLOGY

SOLID MASONRY SAWS
FOR UNIVERSAL CONSTRUCTION JOB SITE USE

- The water spray system ensures optimum saw blade cooling and the immediate removal of the sawing debris with the lowest water consumption and also complies with the current safety standard
- Table saw with swivelling cutting head
- High-quality, low-maintenance construction
- Welded steel construction and plastic water basin with exact table support for accurate cuts
- The adjustable saw head also allows chop cuts
- Foldable table legs for fast and compact transport
- Standard wheelset makes it easier to move on site and to load in a vehicle
- Rolling table equipped with safety gear and lock
- Integrated water pumps - transport lock
- Removable spray protection
- Rear sloping and removable water pan
- Rubberised saw table for non-slip cuts
- Best transport facility by rear and front welded handle
- Exact, smooth cutting table with adjustable angle stop
- Easy saw blade change through the hinged saw hood cover
- ON / OFF switch with EMERGENCY STOPuser-friendly in a protected position





Foldable table legs



Standard wheelset



Adjustable saw head

TECHNICAL DATA	DTS 402
cutting depth standard/max.	110 mm / 135 mm
cutting depth standard/max. 45°	80 mm / 105 mm
cutting length	800 mm
saw blade Ø standard/max.	350 mm / 400 mm
saw blade holder	25,4 mm
output power max.	2.2 kW
voltage	230 V / 50 Hz
saw blade speed	2800 ^{1}/min.
protection class	IP 54
mitre cuts	45°
dimensions (L/W/H)	1200/800/1290 mm
weight	84 kg

DIAMOND TOOLS RECOMMENDATION

Concrete	TL BETON LASER
Natural stone	GSWL 21

MASONRY SAWS	NR.
DTS 402 without diamond blade	1059422

ACCESSORIES	NR.
DTS 402 - adapter cable 2m plug Schuko I coupl. CEE 3-pin 16 A	822312
DTS 402 - adapter cable 2m plug CH Typ12 I coupl. Schuko	822311
DTS 402 - adapter cable 2m plug CEE 3-pin 16 A I coupl. Schuko	822310

Subject to technical change without notice
LISSMAC / 12.2019